

# Grizzly<sup>®</sup> Industrial

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

## Introducing the Grizzly Model G0675 10" Jointer/Planer



### **MACHINE HIGHLIGHTS** (see *Machine Data Sheet* for full specifications)

- 2.5 HP, 220V, single-phase motor.
- Two machines in one—converts from a jointer to a planer in less than a minute!
- Vulcanized rubber planer feed rollers grip strongly, yet are gentle on workpiece surfaces.
- Planes workpieces up to 9¾" wide by 8¼" thick, and joints workpieces as wide as 10¼".
- Designed in Germany, built tough, and manufactured to rigid European standards.

The Model G0675 10" Jointer/Planer is available for \$1,050.00. As with all Grizzly products, the Model G0675 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit [www.grizzly.com](http://www.grizzly.com).



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

## MODEL G0675 JOINTER/PLANER COMBINATION MACHINE

### Product Dimensions:

Weight .....317 lbs.  
Length/Width/Height .....46" x 27" x 38"  
Foot Print (Length/Width).....26" x 22"

### Shipping Dimensions:

#### Carton #1

Type ..... Wood Crate  
Content..... Machine  
Weight .....348 lbs.  
Length/Width/Height..... 44" x 25" x 25"

#### Carton #2

Type ..... Cardboard  
Content..... Base  
Weight .....30 lbs.  
Length/Width/Height..... 29" x 14" x 7"

### Electrical:

Switch..... On/Off Buttons  
Switch Voltage ..... 220V  
Recommended Cord Gauge..... 14 Gauge  
Recommended Breaker Size ..... 15A  
Plug ..... NEMA 6-15

### Motors:

#### Main

Type ..... TEFC Capacitor Start Induction  
Horsepower..... 2.5 HP  
Voltage ..... 220V  
Phase..... Single  
Amps ..... 9.9A  
Speed..... 3400 RPM  
Cycle ..... 60 Hz  
Number Of Speeds ..... 1  
Power Transfer ..... Poly V-Belt  
Bearings ..... Shielded and Lubricated

### Main Specifications:

#### Fence Information

Fence Length .....35<sup>7</sup>/<sub>16</sub>"  
Fence Height.....5<sup>7</sup>/<sub>8</sub>"  
Fence Stops..... 45 and 90 deg.

#### Cutting Capacities (Jointer)

Bevel Jointing ..... 0-45 deg.  
Maximum Width of Cut ..... 10<sup>1</sup>/<sub>4</sub>"  
Maximum Depth of Cut ..... <sup>1</sup>/<sub>8</sub>"  
Number of Cuts Per Minute ..... 13000

**Cutting Capacities (Planer)**

Maximum Width of Cut .....	9 <sup>3</sup> / <sub>4</sub> "
Maximum Depth of Cut Planing Full Width.....	<sup>3</sup> / <sub>16</sub> "
Number of Cuts Per Minute .....	13000
Number of Feed Speeds.....	1
Feed Speed .....	16 FPM
Minimum Stock Length .....	11 <sup>13</sup> / <sub>16</sub> "
Maximum Stock Thickness .....	8 <sup>1</sup> / <sub>4</sub> "

**Knife Information (Jointer)**

Number of Knives .....	2
Knife Type.....	HSS
Knife Length.....	10 <sup>1</sup> / <sub>4</sub> "
Knife Width.....	<sup>11</sup> / <sub>16</sub> "
Knife Thickness.....	<sup>1</sup> / <sub>8</sub> "
Knife Adjustment.....	Jack Screws

**Cutterhead Information**

Cutterhead Type .....	2 HSS Knives
Cutterhead Diameter.....	2 <sup>9</sup> / <sub>32</sub> "
Cutterhead Speed.....	6500 RPM

**Table Information (Jointer)**

Table Length .....	40 <sup>15</sup> / <sub>16</sub> "
Table Width .....	12 <sup>1</sup> / <sub>2</sub> "
Floor To Table Height .....	33 <sup>3</sup> / <sub>4</sub> "

**Table Information (Planer)**

Table Length .....	23 <sup>1</sup> / <sub>8</sub> "
Table Width .....	9 <sup>3</sup> / <sub>4</sub> "
Table Thickness .....	1 <sup>1</sup> / <sub>2</sub> "
Floor To Table Height .....	23"-30"

**Construction**

Body Assembly Construction .....	Sheet Metal
Cutterhead Assembly Construction .....	Steel
Infeed Roller Construction .....	Steel w/Vulcanized Rubber Coating
Outfeed Roller Construction.....	Steel w/Vulcanized Rubber Coating
Jointer Table Construction .....	Cast Iron
Paint.....	Powder Coated

**Other Information**

Dust Port Size .....	4"
Number of Dust Ports .....	1
Measurement Scale (Jointer).....	mm
Measurement Scale (Planer) .....	mm

**Other Specifications:**

Country Of Origin .....	China
Warranty.....	1 Year
Serial Number Location .....	ID Label on Front of the Stand

**Features:**

- Quick release fence
- Flip up outfeed table and change lever simplify jointer-planer conversion
- Vulcanized rubber feed rollers (planer mode)
- Heavy duty cast iron infeed and outfeed tables, easily and accurately adjustable
- Cutterhead guard adjustable for workpiece height
- Dust hood position adjustable for jointer or planer conversion