



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0514X2B 19" 3 HP EXTREME-SERIES BANDSAW W/ MOTOR BRAKE

Product Dimensions:

Weight..... 427 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 36 x 32 x 76 in.
Footprint (Length x Width)..... 29-1/2 x 17-3/4 in.

Shipping Dimensions:

Type..... Wood Slat Crate
Content..... Machine
Weight..... 512 lbs.
Length x Width x Height..... 34 x 21 x 83 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 12A
Minimum Circuit Size..... 20A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 14 AWG
Plug Included..... Yes
Included Plug Type..... 6-20
Switch Type..... Control Panel w/Magnetic Switch Protection & Lockout Key

Motors:

Main

Horsepower..... 3 HP
Phase..... Single-Phase
Amps..... 12A
Speed..... 1725 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Belt Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Main Specifications

Bandsaw Size..... 19 in.
Max Cutting Width (Left of Blade)..... 18-1/4 in.
Max Cutting Width (Left of Blade) w/Fence..... 17 in.
Max Cutting Height (Resaw Height)..... 12 in.
Blade Speeds..... 1700, 3500 FPM

Blade Information

Standard Blade Length..... 143 in.
Blade Length Range..... 141-1/2 – 143 in.
Blade Width Range..... 1/8 – 1-1/4 in.
Type of Blade Guides..... Double Ball Bearing
Guide Post Adjustment Type..... Rack & Pinion
Has Quick-Release..... Yes

Table Information

Table Length..... 26-3/4 in.
Table Width..... 19 in.
Table Thickness..... 1-1/2 in.
Table Tilt..... Left 5, Right 45 deg.
Table Tilt Adjustment Type..... Rack & Pinion
Floor-to-Table Height..... 37-1/2 in.
Fence Locking Position..... Front
Fence is Adjustable for Blade Lead..... Yes
Resaw Fence Attachment Included..... Yes
Miter Gauge Included..... Yes

Miter Gauge Information

Miter Angle..... 0 - 60 deg. L/R
Miter Gauge Slot Type..... T-Slot
Miter Gauge Slot Width..... 3/4 in.
Miter Gauge Slot Height..... 3/8 in.

Construction Materials

Table..... Precision Ground Cast Iron
Trunnion..... Cast Iron
Fence..... Cast Iron
Base/Stand..... Pre-Formed Steel
Frame/Body..... Pre-Formed Steel
Wheels..... Computer-Balanced Cast Iron
Tire..... Polyurethane
Wheel Cover Pre-Formed Steel
Paint Type/Finish..... Powder Coated

Other Related Information

Wheel Diameter..... 18-7/8 in.
Wheel Width..... 1-1/4 in.
Number of Dust Ports..... 2
Dust Port Size..... 4 in.
Compatible Mobile Base..... D2058A

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 1 Hour
Serial Number Location ID Label
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) Yes

Features:

- Ball Bearing Blade Guides
- Green and Putty Powder-Coat Paint
- Blade Tension Indicator
- Blade Tracking Window
- Quick Change Blade Release/Tensioner
- Magnifying Window Over Fence Scale
- Two 4 in. Dust Ports
- Hinged Wheel Covers with Safety Lock
- Micro-Adjusting Rack & Pinion Table Tilt
- Height Scale Measurement
- Included 3/4 in. Blade
- Included Miter Gauge
- Cast-Iron Table Trunnion
- Deluxe Cast-Iron Fence with Extruded Aluminum Resaw Fence Attachment
- Computer Balanced Cast-Iron Wheels with Grizzly Bear Head Cut-Outs
- Rack & Pinion Upper Blade Guide Height Adjustment
- Motor Stops in Under 3 Seconds After Switch is Turned Off