



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0555LANV 14" DELUXE BANDSAW - ANNIVERSARY EDITION

Product Dimensions:

Weight..... 229 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 27 x 30 x 67-1/2 in.
Footprint (Length x Width)..... 23-1/2 x 16-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard Box
Content..... Machine
Weight..... 205 lbs.
Length x Width x Height..... 46 x 22 x 19 in.

Carton #2

Type..... Cardboard Box
Content..... Stand
Weight..... 42 lbs.
Length x Width x Height..... 29 x 24 x 9 in.

Electrical:

Power Requirement..... 110V or 220V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Full-Load Current Rating..... 11A at 110V, 5.5A at 220V
Minimum Circuit Size..... 15A
Power Cord Included..... Yes
Power Cord Length..... 10 ft.
Power Cord Gauge..... 16 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Recommended Plug Type..... 6-15 for 220V
Switch Type..... ON/OFF Push-Button Switch w/Padlock

Motors:

Main

Horsepower..... 1 HP
Phase..... Single-Phase
Amps..... 11A/5.5A
Speed..... 1725 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Belt Drive
Bearings..... Shielded & Permanently Sealed
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Main Specifications

Bandsaw Size.....	14 in.
Max Cutting Width (Left of Blade).....	13-1/2 in.
Max Cutting Width (Left of Blade) w/Fence.....	11-7/8 in.
Max Cutting Height (Resaw Height).....	6 in.
Blade Speeds.....	1800, 3100 FPM

Blade Information

Standard Blade Length.....	93-1/2 in.
Blade Length Range.....	92-1/2 – 93-1/2 in.
Blade Width Range.....	1/8 – 3/4 in.
Type of Blade Guides.....	Ball Bearing
Guide Post Adjustment Type.....	Manual
Has Quick-Release.....	Yes

Table Information

Table Length.....	14 in.
Table Width.....	14 in.
Table Thickness.....	1-1/2 in.
Table Tilt.....	Left 10, Right 45 deg.
Table Tilt Adjustment Type.....	Manual
Floor-to-Table Height.....	43 in.
Fence Locking Position.....	Front
Fence is Adjustable for Blade Lead.....	Yes
Resaw Fence Attachment Included.....	No
Miter Gauge Included.....	Yes

Construction Materials

Table.....	Precision Ground Cast Iron
Trunnion.....	Aluminum
Fence.....	Deluxe Extruded Aluminum
Base/Stand.....	Pre-Formed Steel
Frame/Body.....	Cast Iron
Wheels.....	Computer-Balanced Cast Iron
Tire.....	Rubber
Wheel Cover	Pre-Formed Steel
Paint Type/Finish.....	Powder Coating & Ure

Other Related Information

Wheel Diameter.....	13-3/4 in.
Wheel Width.....	1-3/16 in.
Number of Dust Ports.....	1
Dust Port Size.....	4 in.
Compatible Mobile Base.....	D3757

Other Specifications:

Country of Origin	Taiwan
Warranty	1 Year
Approximate Assembly & Setup Time	1-1/2 Hours
Serial Number Location	ID Label on Top Cover
ISO 9001 Factory	No
Certified by a Nationally Recognized Testing Laboratory (NRTL)	Yes

Features:

- Deluxe Heavy-Duty Stand
- Upper & Lower Ball-Bearing Blade Guides
- All Ball-Bearing Construction
- 4" Dust Port
- Includes 3/8" Blade
- Includes Fence and Miter Gauge
- Quick-Release Blade Tension Lever
- Fence Scale With Magnifying Window