



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0564 OSCILLATING EDGE SANDER 3 HP

Product Dimensions:

Weight..... 495 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 60 x 28 x 49 in.
Footprint (Length x Width)..... 32 x 19-1/2 in.

Shipping Dimensions:

Type..... Wood Crate
Content..... Machine
Weight..... 597 lbs.
Length x Width x Height..... 58 x 31 x 44 in.

Electrical:

Power Requirement..... 240V, Single-Phase, 60 Hz
Prewired Voltage..... 240V
Full-Load Current Rating..... 18A
Minimum Circuit Size..... 20A
Switch..... Magnetic Contactor and Overload Relay
Switch Voltage..... 220V
Cord Length..... 10 ft.
Cord Gauge..... 12 AWG
Plug Included..... No
Recommended Plug/Outlet Type..... NEMA 6-20

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 3 HP
Voltage..... 240V
Phase..... Single
Amps..... 18A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Direct Drive
Bearings..... Shielded and Permanently Lubricated

Main Specifications:

Operation Information

Sanding Belt Speed..... 3150 FPM
Sanding Belt Oscillations..... 3/4 in.
Sanding Belt Length..... 108 in.
Sanding Belt Width..... 6 in.
Sanding Belt Tilt..... 0 - 90 deg.

Table Information

| | |
|----------------------------|---------------------|
| Table Length..... | 35-1/2 in. |
| Table Width..... | 12 in. |
| Table Thickness..... | 1-1/2 in. |
| Table Travel..... | 4 in. |
| Floor To Table Height..... | 35-3/4 - 39-3/4 in. |
| End Table Length..... | 11-1/2 in. |
| End Table Width..... | 10 in. |
| End Table Thickness..... | 3/4 in. |
| End Table Travel..... | 10 in. |

Platen Information

| | |
|--------------------|------------------------|
| Platen Type..... | Steel wih Graphite Pad |
| Platen Length..... | 39-3/4 in. |
| Platen Width..... | 6-3/4 in. |
| Platen Travel..... | 0 - 90 deg. |

Construction

| | |
|-------------------|----------------------------|
| Table..... | Precision Ground Cast Iron |
| Frame..... | Sheet Metal |
| Base..... | Sheet Metal |
| Drive Roller..... | Aluminum |
| Idler Roller..... | Rubber |
| Miter Block..... | Aluminum |
| Paint..... | Powder Coated |

Other Related Information

| | |
|------------------------|---------------------|
| No Of Dust Ports..... | 2 |
| Dust Port Size..... | 4 in. |
| Belt Release..... | Quick Release Lever |
| Drive Roller Size..... | 7 in. |
| Idler Roller Size..... | 3-7/8 in. |

Other Specifications:

| | |
|------------------------------|-------------|
| Country Of Origin | Taiwan |
| Warranty | 1 Year |
| Serial Number Location | On the Base |
| Assembly Time | 10 Minutes |
| Sound Rating | 90 dB |

Features:

- Sanding Surfaces Tilts Vertical and Horizontal
- T-Slot Table and Miter Gauge
- Quick Belt Release Lever
- Graphite Coated Platen
- Oscillating Sanding Surfaces
- Sanding Belt Oscillates at 52 Cycles per Minute
- Includes 3 Sanding Drums: 1 1/2", 2", 3" x 4 1/2"
- Platen Tilts 0 to 90 degrees (5 deg. Scale)