



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1495 HEAVY-DUTY WOOD LATHE

Product Dimensions:

Weight..... 262 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 68 x 12-1/2 x 48 in.
Footprint (Length x Width)..... 57 x 10 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard
Content..... Machine
Weight..... 192 lbs.
Length x Width x Height..... 59 x 23 x 12 in.

Carton #2

Type..... Cardboard
Content..... Stand
Weight..... 89 lbs.
Length x Width x Height..... 22 x 11 x 31 in.

Electrical:

Minimum Circuit Size..... 15 amp
Switch..... Paddle
Switch Voltage..... 110V
Cord Length..... 6 ft.
Cord Gauge..... 18 gauge
Plug Included..... Yes

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 3/4 HP
Voltage..... 110/220V
Prewired..... 110V
Phase..... Single
Amps..... 12/6A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Belt Drive
Bearings..... Shielded and Lubricated

Main Specifications:

Operation Information

Swing Over Bed..... 14 in.
Dist Between Centers..... 40 in.
Swing Over Gap..... 17 in.
Swing Over Tool Rest..... 10 in.
No of Spindle Speeds..... 7
Spindle Speeds..... 500, 580, 750, 1100, 1550, 2200, 3070 RPM
Floor to Center Height..... 41-1/2 in.

Spindle Information

Spindle Type..... Right Hand
Spindle Taper..... MT#2
Spindle Size..... 1 in.
Spindle Bore..... 0.388 in.
Spindle Center..... Spur
Spindle TPI..... 12
Indexed Spindle..... 30 deg.
No of Indexes..... 12
Outboard Spindle Type..... Left Hand
Outboard Spindle Size..... 7/8 in.
Outboard Spindle TPI..... 16

Tailstock Information

Tailstock Taper..... MT#2
Tailstock Center..... Live

Construction

Bed..... Precision Ground Cast Iron
Frame..... Cast Iron
Stand..... Preformed Sheet Steel
Base..... Formed Steel
Headstock..... Cast Iron
Sanding Table..... Cast Aluminum
Tailstock..... Cast Iron
Paint..... Powder Coated

Other Related Information

Bed Width..... 5-1/2 in.
Faceplate Size..... 6 in.
Sanding Disc Size..... 8 in.

Other Specifications:

Country Of Origin Taiwan
Warranty 1 Year
Serial Number Location
Awards Popular Woodworking Reader's Choice
Assembly Time 45 minutes

Features:

- Indexed Spindle Every 30 deg.
- Work Shield
- Includes Cabinet Stand with Shelves
- Cast Iron Bed
- Variable Speed
- Paddle Switch with Safety Key
- All Ball Bearing

Accessories Included:

- 4" x 6" Pneumatic Drum Sander
- 6" Face Plate
- 8" Sanding Disc
- Flap Sander
- Live Center
- Miter Gauge
- Outboard Tool Rest
- Spur Center