



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL H0796 POWER FEEDER FOR BANDSAWS

Product Dimensions:

Weight..... 61 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 43-1/2 x 8-1/2 x 13 in.
Footprint (Length x Width)..... N/A x N/A

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 66 lbs.
Length x Width x Height..... 29 x 11 x 16 in.
Must Ship Upright..... No

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 1.55A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 9 ft.
Power Cord Gauge..... 16 AWG
Plug Included..... No

Motors:

Main

Horsepower..... 1/4 HP
Phase..... Single-Phase
Amps..... 1.55A/1.1A
Speed..... 3400 / 1735 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Belt Drive
Bearings..... Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type..... N/A

Main Specifications:

Operation Info

Number of Feed Speeds..... 6
Feed Speeds..... 4.4, 8.9, 12, 12.5, 24.3, 36 FPM
Swing..... 15 deg.
Horizontal Movement..... 9 in.
Rotation..... Forward

Roller Info

Number of Rollers..... 3
Roller Width..... 2 in.
Roller Diameter..... 4 in.
Centers Between Rollers..... 2-1/2 in.

Construction Info

Roller..... Serrated Steel
Housing..... Cast Aluminum
Supports..... Cast Iron
Column..... Steel
Paint Type/Finish..... Enamel

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 30 Minutes
Serial Number Location Checked Sticker, On Feeding Roller Cover
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

Roller is Spring Tensioned
Heavy-Duty Gear Reduction with Hardened Gears
Spring Loaded Aluminum Toothed Drive Rollers Adjust for Various Thicknesses