



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL H0796 POWER FEEDER FOR BANDSAWS

Product Dimensions:

Weight..... 61 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 43-1/2 x 8-1/2 x 13 in.
Footprint (Length x Width)..... N/A x N/A

Shipping Dimensions:

Type..... Cardboard
Content..... Machine
Weight..... 66 lbs.
Length x Width x Height..... 29 x 11 x 16 in.

Electrical:

Minimum Circuit Size..... 10 amp
Switch Voltage..... 220V
Cord Length..... 9 ft.
Cord Gauge..... 16 gauge
Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 1/4 HP
Voltage..... 220V
Prewired..... 220V
Phase..... Single
Amps..... 1.55/1.1A
Speed..... 3400/1735 RPM
Cycle..... 60 Hz
Number of Speeds..... 2
Power Transfer Belt Drive
Bearings..... Lubricated for Life

Main Specifications:

Operation Info

No. Of Feed Speeds..... 6
Feed Speeds..... 4.4, 8.9, 12, 12.5, 24.3, 36 FPM
Swing..... 15 deg.
Horizontal Movement..... 9 in.
Rotation..... Forward

Roller Info

No. Of Rollers..... 3
Roller Width..... 2 in.
Roller Diameter..... 4 in.
Centers Between Rollers..... 2-1/2 in.

Construction Info

Roller..... Serrated Steel
Housing..... Cast Aluminum
Supports..... Cast Iron
Column..... Steel
Paint..... Epoxy

Other Specifications:

ISO Factory ISO 9001
Country Of Origin Taiwan
Warranty 1 Year
Serial Number Location "Checked" Sticker, On Feeding Roller Cover
Assembly Time 20 minutes

Features:

Roller is Spring Tensioned
Heavy-Duty Gear Reduction with Hardened Gears
Spring Loaded Aluminum Toothed Drive Rollers Adjust for Various Thicknesses